

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at www.onsemi.com

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, emplo



November 2006

MJD112


NPN Silicon Darlington Transistor

Features

- High DC Current Gain
- Built-in a Damper Diode at E-C
- Lead Formed for Surface Mount Applications (No Suffix)



1.Base 2.Collector 3.Emitter



Absolute Maximum Ratings* $T_a = 25$ °C unless otherwise noted

Symbol	Parameter	Value	Units
V _{CBO}	Collector-Base Voltage	100	V
V _{CEO}	Collector-Emitter Voltage	100	V
V _{EBO}	Emitter-Base Voltage	5	V
I _C	Collector Current (DC)	2	A
I _{CP}	Collector Current (Pulse)	4	А
I _B	Base Current	50	mA
P _C	Collector Dissipation (T _C =25°C)	20	W
	Collector Dissipation (T _a =25°C)	1.75	W
T _J	Junction Temperature	150	°C
T _{STG}	Storage Temperature	- 65 ~ 150	°C

^{*} These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

Electrical Characteristics* T_a=25°C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Max.	Units
V _{CEO} (sus)	Collector-Emitter Sustaining Voltage	$I_C = 30 \text{mA}, I_B = 0$	100		V
I _{CEO}	Collector Cut-off Current	$V_{CE} = 50V, I_{B} = 0$		20	μА
I _{CBO}	Collector Cut-off Current	$V_{CB} = 100V, I_B = 0$		20	μΑ
I _{EBO}	Emitter Cut-off Current	$V_{EB} = 5V, I_{C} = 0$		2	mA
h _{FE}	* DC Current Gain	$V_{CE} = 3V, I_{C} = 0.5A$ $V_{CE} = 3V, I_{C} = 2A$ $V_{CE} = 3V, I_{C} = 4A$	500 1000 200	12K	
V _{CE} (sat)	* Collector-Emitter Saturation Voltage	$I_C = 2A, I_B = 8mA$ $I_C = 4A, I_B = 40mA$		2 3	V V
V _{BE} (sat)	* Base-Emitter Saturation Voltage	$I_C = 4A, I_B = 40mA$		4	V
V _{BE} (on)	* Base-Emitter On Voltage	$V_{CE} = 3A, I_{C} = 2A$		2.8	V
f _T	Current Gain Bandwidth Product	$V_{CE} = 10V, I_{C} = 0.75A$	25		MHz
C _{ob}	Output Capacitance	$V_{CB} = 10V, I_{E} = 0$ f = 0.1MHz		100	pF

^{*} Pulse Test: Pulse Width \leq 300 μ s, Duty Cycle \leq 2%

Typical Characteristics




Figure 1. DC current Gain




Figure 3. Collector Output Capacitance




Figure 5. Turn Off Time




Figure 2. Base-Emitter Saturation Voltage Collector-Emitter Saturation Voltage




Figure 4. Turn On Time




Figure 6. Safe Operating Area

Typical Characteristics (Continued)





Figure 1. Power Derating

Mechanical Dimensions

D-PAK



Dimensions in Millimeters

4

UltraFET[®]

UniFET™

 VCX^{TM}

Wire™



FAIRCHILD SEMICONDUCTOR TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

 OCX^{TM} SILENT SWITCHER® ACEx™ FACT Quiet Series™ OCXPro™ ActiveArray™ GlobalOptoisolator™ SMART START™ OPTOLOGIC® Bottomless™ GTO™ SPM™ OPTOPLANAR™ HiSeC™ Stealth™ Build it Now™ I^2C^{TM} PACMANTM CoolFET™ SuperFET™ РОР™ $CROSSVOLT^{rm}$ i-LoTM SuperSOT™-3 ImpliedDisconnect™ Power247™ SuperSOT™-6 **DOME™** EcoSPARK™ PowerEdge™ IntelliMAX™ SuperSOT™-8 E²CMOSTM PowerSaver™ ISOPLANAR™ SyncFET™ PowerTrench® TCM^TM EnSigna™ LittleFET™ QFET® **FACT®** $\mathsf{MICROCOUPLER}^{\mathsf{TM}}$ TinyBoost™ TinyBuck™ $\mathsf{FAST}^{\mathbb{R}}$ QSTM MicroFET™ FASTr™ QT Optoelectronics™ TinyPWM™ MicroPak™ FPS™ Quiet Series™ MICROWIRE™ TinyPower™ FRFET™ MSXTM RapidConfigure™ TinyLogic[®] RapidConnect™ TINYOPTO™ MSXPro™ uSerDes™ TruTranslation™ Across the board. Around the world.™ ScalarPump™ **UHC®**

The Power Franchise®

Programmable Active Droop™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPE-CIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

Rev. I21

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdt/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and exp

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81–3–5817–1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative